



Innen- und Aussenkuehlung / Inside and outside coolant supply  
Kuehlmittelfiltrierung-50 $\mu$  / coolant filtration-50 $\mu$

Bemerkung - Note  
Für Trockenlauf geeignet!  
Use without coolant fluid allowed!

| Technische Daten - technical data |                       |
|-----------------------------------|-----------------------|
| Weight                            | = 14,318 [kg]         |
| Torque max. (M1/M2)               | = 80 / 80 [Nm]        |
| Speed max. (n1/n2)                | = 6000 / 6000 [1/min] |
| Gear ratio (i)=n1:n2              | = 1:1                 |
| Pressure (pmax)                   | = 70 [bar]            |

Benennung - Title  
**Radial Bohr und Fräskopf, zurückges**  
**Radial drill. and mill. head offset**

|  |  |   |  |
|--|--|---|--|
|  | <small>EWS Weigle GmbH &amp; Co. KG<br/>Maybachstr. 1<br/>D-73066 Uhlingen<br/>www.ews-tool.de</small> | <small>Technische Änderungen vorbehalten!<br/>Subject to technical modifications!</small> |  |
|  | <small>Nr. - No.</small><br>80.65VX4VL6FIKD-CC4  | <small>IDENT: DEWS259346</small>  |  |



Copyright **EWS Tool Technologies**  
Weitergabe und Vervielfältigung dieser Unterlage,  
Verwertung und Mitteilung ihres Inhalts nicht  
gestattet, soweit nicht ausdrücklich zugestanden.  
Zuwerhandlungen verpflichten zu Schadenersatz.