



Innen- und Aussenkuehlung / Inside and outside coolant supply  
Kuehlmittelfiltrierung=50µ / coolant filtration=50µ

Bemerkung - Note  
Für Trockenlauf geeignet!  
Use without coolant fluid allowed!

| Technische Daten - technical data |                        |
|-----------------------------------|------------------------|
| Weight                            | = 8.790 [kg]           |
| Torque max. (M1/M2)               | = 50 / 25 [Nm]         |
| Speed max. (n1/n2)                | = 6000 / 12000 [1/min] |
| Gear ratio (i)=n1:n2              | = 1:2                  |
| Pressure (pmax)                   | = 70 [bar]             |

Benennung - Title  
**Radial Bohr und Fräskopf**  
**Radial drilling and milling head**

|  |   |  |  |
|--|---|--|--|
|  | <small>EWS Weigle GmbH &amp; Co. KG<br/>Maybachstr. 1<br/>D-73066 Uhlingen<br/>www.ews-tools.de</small> | <small>Technische Aenderungen vorbehalten!<br/>Subject to technical modifications!</small> |  |
|  | <small>Nr. - No.</small><br><b>60.40VX4SQT15RIKD1</b>   | <small>IDENT: DEWS258425</small>   |  |

Copyright **EWS Tool Technologies**  
Weitergabe und Vervielfaeltigung dieser Unterlage,  
Verwertung und Mitteilung ihres Inhalts nicht  
gestattet, soweit nicht ausdrecklich zugestanden.  
Zuwoerhandlungen verpflichten zu Schadenersatz.