



Bemerkung - Note Nicht ohne Kuehlmittel betreiben! Not for use without coolant-fluid!		Technische Daten - technical data M1 / M2 = 50 /25 Nm n1 / n2 = 6000 /12000 1/min i (N1:N2) = 1:2 pmax = 70 bar		Benennung - Title Axial Bohr u. Fräskopf achsversetzt Ax. drill. and mill. head offset		<table><tr><td></td><td>name</td><td>date</td></tr><tr><td>drawing</td><td></td><td>07.02.2007</td></tr><tr><td colspan="3"><div><div>EWS</div><div>Tool Technologies</div></div><div>EWS Weigle GmbH & Co. KG Maybachstr. 1 D-73066 Uehingen Tel. +49(0)7161/93040-100</div></td></tr></table>			name	date	drawing		07.02.2007	<div><div>EWS</div><div>Tool Technologies</div></div> <div>EWS Weigle GmbH & Co. KG Maybachstr. 1 D-73066 Uehingen Tel. +49(0)7161/93040-100</div>			Technische Aenderungen vorbehalten! Subject to technical modifications!		<div><div></div><div></div></div>	
	name	date																		
drawing		07.02.2007																		
<div><div>EWS</div><div>Tool Technologies</div></div> <div>EWS Weigle GmbH & Co. KG Maybachstr. 1 D-73066 Uehingen Tel. +49(0)7161/93040-100</div>																				
						Nr. 50.40321809RIK11		DIN A3												
						MNR: 159052		IDENT: D-EWS-000588 -		Blatt - page 1 (1)										